

## AGILE



Chilled Food Dispatch Lines

## CORE



Multi-Purpose Processing Lines

## TITAN



High-Friction Industrial Zones

Suitable For	Chilled Food Dispatch Lines	Multi-Purpose Processing Lines	High-Friction Industrial Zones
Features	Flexible, Cold-Rated	Universal, Versatile	Heavy-Duty, Abrasion-Resistant
Hose Structure	4 layers	4 layers	5 layers
Temperature Range	-5°C / ±70°C	-20°C / ±90°C	-35°C / ±135°C
Internal Diameter	12mm	12mm	12.5mm
External Diameter	22mm	22mm	22mm
Layer Thickness	5mm	5mm	4.75mm
23°C Working Pressure	80bar	80bar	125bar
23°C Bursting Pressure	240bar	240bar	375bar
90°C Working Pressure	40bar	40bar	80bar
90°C Bursting Pressure	120bar	120bar	240bar
Bending Radius	120mm	120mm	90mm
Bending Length	25m	25m	25m
Nominal Weight Per Meter	330g	320g	345g

Sizes Available      MOQ  
 30m, 60m, 100m      10

All hoses are complete with male/female ends, not including taps and nozzles

**Domestic Food-Grade**      All hoses comply with GB4806.7-2023 food contact safety standard

**International Food-Grade**      All hoses are FDA approved and meet international food contact safety specs

**Environmental Standard**      All hoses comply with RoHS, and restricts lead, mercury, etc., eco-friendly